

DigiCAM-50 Medium Format Aerial Camera





DIGICAM is a result of the IGI's passion for airborne developments. It is an aerial digital camera system in medium format, providing professional photogrammetry.

The *DigiCAM* combined with *CCNS-5* and *AEROcontrol* provides the complete solution for generating directly georeferenced images on a planned mission.

Highlights

- 50 MP resolution
- Up to 0.6 sec frame rate, high shutter speed up to 1/2500 sec
- FMC by BCM
- High Dynamic Range 84dB
- Phase One Camera Module with CMOS Sensor Technology
- IGI SMU-2 (Sensor Management Unit)
- Up to 4TB hot-swap Storage Units with IGI Redundant Storage Technology
- Integrated Sensor Management (IGIvisu)
- IGI FRAMEtrack: real-time, geo-referenced imagery previews during the flight
- IGI IPS: Image Processing Software with export to standard formats
- Integrated GNSS/IMU System (AEROcontrol)
- Integrated Mission Planning & Flight Guidance (CCNS-5 with IGIplan)
- 10" or 20" Operator Touch-Screen
- Upgradeable to multi DigiCAM systems e.g. IGI Penta-DigiCAM or IGI UrbanMapper
- Support for custom installations and combinations with IGI LiteMapper, Airborne LiDAR Systems

IGI DigiCAM[®] - Specifications

SPECIFICATIONS IGI DigiCAM-50		
Image Size	8,280 x 6,208 pixels, 50 MP	
Channels	RGB	
Sensor Technology	CMOS	
Pixel Size	5.3 μm	
Maximum Frame Rate	0.6 sec	
Dynamic Range	84 dB	
Compensation	FMC by BCM	
SSD Hot-plug Storage Units with IGI Redundant Storage Technology	Storage Units for >50,000 images (4, 2, 1, 0.5 TB)	
Lenses	32, 40, 50, 70, 90mm Rodenstock, 110, 150, 180, 300mm Schneider-Kreuznach	

SPECIFICATIONS IGI DigiCAM			
Shutter	Electronically controlled leaf shutter, up to 1/2500 sec		
Analog to Digital Conversion	16 bit		
Maximum Operating Altitude	No limit		
System Weight	DigiCAM-50 Camera Head with 50 mm Lens	1.8 kg (4.0 lbs)	
	DigiCAM-50 Camera Head with 80 mm Lens	1.1 kg (2.4 lbs)	
	IGI DigiControl with Storage Unit	1.9 kg (4.1 lbs)	
	10" Operator Touch-Screen 20" Operator Touch-Screen	1.2 kg (2.7 lbs) 2.4 kg (5.3 lbs)	
	Cabeling, Antenna, etc.	0.5 kg (1.1 lbs)	
Power Consumption	DigiCAM-50 Camera Module	16W @ 30 VDC	
	DigiCAM-50 Camera Module	14W @ 30 VDC	
	IGI DigiControl with Storage Unit	30W @ 28 VDC	
	10" Operator Touch-Screen 20" Operator Touch-Screen	22W @ 28 VDC 80W @ 28 VDC	

+49 (0)2732 5525-0

info@igi-systems.com

+49 (0)2732 5525-25 () www.igi-systems.com

IGI mbH Langenauer Str. 46 57223 Kreuztal Germany